

SUZUKI STROM 250 SX

SPECIFICATIONS

	Engine type	4-stroke, single-cylinder, oil-cooled, SOHC
	Valve system	4 valve
	Displacement	249 cm ³
	Bore x Stroke	76 mm x 54.9 mm
	Compression ratio	10.7 : 1
Engine	Max power	26.5ps@9300rpm
	Max torque	22.2Nm@7300rpm
	Fuel system	Fuel Injection
	Starter system	Electric
	Transmission	6-speed constant mesh
	Lubrication system	Wet sump
	Overall length	2180 mm
	Overall width	880 mm
Dimension	Overall height	1355 mm
and Weight	Wheelbase	1440 mm
	Ground clearance	205 mm
	Seat height	835 mm
	Kerb mass	167 kg
	Fuel tank capacity	12 L
Suspension	Front	Telescopic, coil spring, oil damped
	Rear	Swingarm type, coil spring, oil damped
Brakes	Front	Disc, single
	Rear	Disc
Tyres	Front	100/90-19M/C 57S, tubeless
	Rear	140/70-17M/C 66S, tubeless
Rake / Trail		27° / 97 mm
Electrical	lgnition system	Electronic ignition
	Battery	Maintenance free, 12V 6Ah
	Headlight & Tail light	LED









Pearl Blaze Orange (QVN)



Glass Sparkle Black (YVB)



Bell Village 405 1000 Flacq 405 1088 Forbach 405 1110 Rodrigues 831 0592